

BC1601D



Feature

1. COB with metal frame
2. 5x7 dots with cursor
3. Built-in controller KS0066 or equivalent
4. + 5V single power supply
5. 1/16 duty cycle
6. LED B/L pins: 15/16, or A/K or 1/2
7. Option: LED B/L
8. Option: +3V single power supply
9. Option: negative voltage (built-in, external)



Mechanical Data

Item	Standard Value	Unit
Module Dimension	122.0 x 33.0	mm
Viewing Area	99.0 x 13.0	mm
Dot Size	0.92 x 1.16	mm
Character Size	4.84 x 9.7	mm



Pin Assignment

Pin	Symbol	Function
1	Vss	GND
2	Vdd	+5V(+3V option)
3	Vo	Contrast adjustment
4	RS	H/L register select signal
5	R/W	H/L read/write signal
6	E	H --> L enable signal
7~14	DB0~7	H/L data bus line
15	A	Power supply for B/L (+)
16	K	Power supply for B/L (GND)

Electronic Characteristics

Item	Symbol	Condition	Typical Value	Unit
Input Voltage	Vdd	Vdd = +5V	5.0	V
Supply Current	Idd	Vdd = +5V	1.2	mA
LCD Driving Voltage	Vdd-Vo	25°C	4.7	V
LED Forward Voltage	Vf	25°C	4.2	V
LED Forward Current	If	25°C	160	mA
EL Power Voltage	Vel	Vel=110 Vac/400Hz	---	V

Dimension



SCALE 3/1